





Feature

- Bright, white light
- Total internal reflector
- IP68 & IP69K
- Low current draw
- Constant current circuit draw
- · Hassle-free installation
- SAE / DOT compliant
- 50,000+ hours LED service life



Benefit

Enhances illumination and reduces driver fatigue.

Improves driver's visibility, enhancing safety.

Will withstand dust, dirt, sand, and water submersion.

Energy efficient, save on fuel costs.

Light does not dim even if voltage fluctuates.

"Drop-in" design easily replaces standard 90mm

headlight systems without any need for retooling.

Compliant to US / CDN federal regulations.

Long lasting investment, quality product.






Specifications

Operating Voltage:	12 - 24Vdc	Weight:	2.0lbs (0.9kg)
Operating Current:	Low Beam:	Housing:	Die Cast Aluminum - Black E-Coat
	1.1A @ 12Vdc		Black Polycarbonate
	0.5A @ 24Vdc	Lens:	Automotive Optical Grade
	High Beam:		Hard-Coated Polycarbonate
	1.2A @ 12Vdc	Connection:	Low Beam: 3 Position Connector
	0.6A @ 24Vdc		High Beam: 2 Position Connector
Power Consumption:	Low Beam: 13W	Polarity:	Reverse Voltage Protected
	High Beam: 14W	Vibration Resistance:	10-500Hz @ 5Grms
Temperature Range:	-40°C to +65°C	Compliance:	FMVSS108 and CMVSS108
Ingress Protection:	IP68 & IP69K	EMC Rated:	EMC EN 13309: 2010


Part #	Description	Operating Voltage
71075	LED Low Beam 90mm	12 - 24Vdc
71079	LED High Beam 90mm	12 - 24Vdc
98135	Adjustment Bolts	

Low Beam



High Beam

3.4" (85mm)



1.5" (37mm)

3.1" (79mm)



