XWL-813 5000 Series | HDM LED WORK LIGHT | 5000 LUMENS







Super tough stainless steel mounting brackets and hardware.

Allows 50° tilt forwards & backwards.



Feature

- Die cast aluminum housing and polycarbonate lens
- IP68 & IP69K
- · Constant current circuit draw
- 3 beam patterns
- · Built-in vibration dampeners
- 50,000+ hours LED service life



Benefit

Virtually unbreakable.

Will withstand dust, dirt, sand, and water submersion.

Light does not dim even if voltage fluctuates.

Get light where it's needed most.

Reduces the intensity of shock and vibration.

Long lasting investment, quality product.







Specifications

Operating Voltage: 12 - 24Vdc
Operating Current: 4.2A @ 12Vdc
2.1A @ 24Vdc

Power Consumption: 50W

Temperature Range: -40°C to +60°C Ingress Protection: IP68 & IP69K Weight: 3.5lbs (1.6kg)

Housing: Die Cast Aluminum - Black E-Coat

Lens: Automotive Optical Grade

Hard-Coated Polycarbonate

Connection: Tyco or Deutsch

Polarity: Reverse Voltage Protected

Vibration Resistance: 10-500Hz @ 5Grms


Mounting: U-Bracket

EMC Rated: EMC EN 13309: 2010

Part #	Beam Pattern	Lumens	Operating Voltage	
Tyco Connector				
81665	Spot	5000	12 - 24Vdc	
81666	Medium Flood	5000	12 - 24Vdc	
81667	Hybrid	5000	12 - 24Vdc	
Deutsch Connector				
81668	Spot	5000	12 - 24Vdc	
81669	Medium Flood	5000	12 - 24Vdc	
81670	Hybrid	5000	12 - 24Vdc	


Accessories


98195 Easy Grip Handle - Black | Blue | Orange




5320 Downey Street | Burlington | Ontario | Canada | L7L 6M2 Tel: 905.332.4094 | Fax: 905.332.9020 | Toll Free: 1.800.567.5483 hamsar.sales@grakon.com | www.hamsar.com ISO9001:2015 | ISO14001:2015

Beam Patterns







Connector Options

