

Premium 90mm LED Low and High Beam HEADLIGHT MODULES



Feature

- Best-in-class output and performance
- 90mm LED headlight modules
- OEM grade specifications
- Projector-style low beam
- Reflector-style high beam
- Functional in both 12V & 24V environments
- ECE & SAE compliant variants
- ECE-R10 compliant
- Common LH and RH mounting features

**Plug-and-play
legal compliance.**



Placed in a custom bezel, a module
can create a completely styled headlight.

Specifications



Operating Voltage:	12 - 24Vdc
Operating Current:	2600mA @ 12Vdc 650mA @ 24Vdc
Power Consumption:	22W
Temperature Range:	-40°C to +80°C
Weight:	Low Beam: 35.1oz (996g) High Beam: 24.6oz (697g)
Source Lumen Output:	1400lm to 1700lm
Transient Susceptibility:	-450V (negative transient) 150V (positive transient)
Electrostatic Discharge:	± 15kV (on surfaces that are exposed during normal operation including service)
Electrostatic Discharge, Unpowered:	± 8kV (all surfaces)
Compliance:	ECE and SAE

Part #	Description	Operating Voltage
76865	LED Low Beam 90mm ECE LHD	12 - 24Vdc
76866	LED High Beam 90mm ECE SAE	12 - 24Vdc
76867	LED Low Beam 90mm ECE RHD	12 - 24Vdc
76868	LED Low Beam 90mm SAE	12 - 24Vdc
98142	Adjustment Bolts	

Low Beam



High Beam


 For more lighting and electronic solutions,
 please check out our catalogue.