## XWL-810 Series COMPACT LED WORK LIGHT | 1260 LUMENS

the work it.



"2 Lives in 1" Mount System

If one attachment point fails due to a collision, rotate to the next channel point and re-mount the light.

# Compact, versatile, heavy duty work light.

Delivers 1260 lumens of bright white illumination.

## (<u>=</u>)

### Feature

- Die cast aluminum housing, polycarbonate lens and high impact bezel
- IP68 & IP69K
- Low current draw
- Constant current circuit draw
- 4 beam patterns
- 50,000+ hours LED service life

Benefit

Virtually unbreakable.

Will withstand dust, dirt, sand, and water submersion. Energy efficient, save on fuel costs.

- Light does not dim even if voltage fluctuates.
- Get light where it's needed most.
- Long lasting investment, quality product.







## Always on.

#### **Specifications**

Beam Patterns

Operating Vo	ltage:	12 - 24Vdc		$\frown$
Operating Cu		1.2A @ 12Vdc		Spot Pattern
		0.6A @ 24Vdc		
Power Consu	mption:	14W		15 (49)
Temperature	Range:	-40°C to +80°C		
Ingress Prote	ction:	IP68 & IP69K		
Weight:		1.3lbs (0.6kg)		
Housing:			m Alloy A380   Black E-Coat	15 (49)
Lens:		Automotive Optic	al Grade	0 15 30 45 60 75 90 105
		Hard-Coated Poly	/carbonate	(49) (98) (147) (196) (245) (294) (343) Distance in Metres (Feet)
Connection:		6" Wire		$\frown$
Polarity:		Reverse Voltage Protected		Wide Flood Pattern
Vibration Resistance:		10-500Hz @ 5Grms		
Mounting:		C-Bracket (Powder Coated Steel)		15 (49)
		Swivel Bracket (Z	inc Dichromate Plating)	
EMC Rated:		EMC EN 13309: 2010		
Part #	Beam Patterr	n Lumens	Operating Voltage	15 (49)
04074	Creat	1260	42 24)//	0 15 30 45 60 75 90 105 (49) (98) (147) (196) (245) (294) (343)
81271	Spot	1260	12 - 24Vdc	Distance in Metres (Feet)
81272 81273	Wide Flood Medium Flood	1260 1260	12 - 24Vdc 12 - 24Vdc	Medium Flood Pattern
		1260		Medium Flood Pattern
81274	Hybrid	1260	12 - 24Vdc	
Swivel Brack	ot			
81275	Spot	1260	12 - 24Vdc	
81276	Wide Flood	1260	12 - 24Vdc	
81277	Medium Flood	1260	12 - 24Vdc	15 (49)
81278	Hybrid	1260	12 - 24Vdc	
01270	riyona	1200		0 15 30 45 60 75 90 105 (49) (98) (147) (196) (245) (294) (343)
Accessories			Ī	Distance in Metres (Feet)
HW02A	Hardware Kit	C-Bracket		Hybrid Pattern
98189		Swivel Bracket	Bolt 1/2"	
98195		lle - Black   Blue	Orange	15 (49)
3.4"	(71	2.8" 1mm)		
← <sup>3.4"</sup> (86mm) →			C-Bracket	
				15 (49)
⋬∕⊛ <sup>⊛</sup> ⊘∖	3.5"			
	(89mm)		CONFERENCE T	0 15 30 45 60 75 90 105 (49) (98) (147) (196) (245) (294) (343) Distance in Metres (Feet)
			a a a a a a a a a a a a a a a a a a a	Cistaire ii menes (ceet)
	1.8" (46mm)	HT -		
	(46mm)	<u> </u>		For more lighting and electronic solutions,
ЦЦJ	T		Swivel Bracket	please check out our catalogue.

5320 Downey Street | Burlington | Ontario | Canada | L7L 6M2 Tel: 905.332.4094 | Fax: 905.332.9020 | Toll Free: 1.800.567.5483 hamsar.sales@grakon.com | www.hamsar.com ISO9001:2015 | ISO14001:2015