XTL-800 Series LED WORK LIGHT | 2500 LUMENS







Delivers 2500 lumens of bright white illumination.



Feature

- Die cast aluminum housing, polycarbonate lens and high impact bezel
- IP68 & IP69K
- Low current draw
- · Constant current circuit draw
- 3 beam patterns
- 50,000+ hours LED service life



Benefit

Virtually unbreakable.

Will withstand dust, dirt, sand, and water submersion.

Energy efficient, save on fuel costs.

Light does not dim even if voltage fluctuates.

Get light where it's needed most.

Long lasting investment, quality product.







Specifications

Operating Voltage: 12 - 24Vdc
Operating Current: 1.8A @ 12Vdc
0.9A @ 24Vdc

Power Consumption: 22W

Temperature Range: -40°C to +80°C Ingress Protection: IP68 & IP69K Weight: 2.2lbs (1.0kg)

Housing: Die Cast Aluminum Alloy A380 | Black E-Coat

Lens: Automotive Optical Grade

Hard-Coated Polycarbonate

Connection: 6" Wire

Polarity: Reverse Voltage Protected

Vibration Resistance: 10-500Hz @ 5Grms

Mounting: C-Bracket (Powder Coated Steel)


Swivel Bracket (Zinc Dichromate Plating)


EMC Rated: EMC EN 13309: 2010

Part #	Beam Pattern	Lumens	Operating Voltage
Black Bezel C-Bracket			
81861/HO	Spot	2500	12 - 24Vdc
81863/HO	Medium Flood	2500	12 - 24Vdc
81881/HO	Hybrid	2500	12 - 24Vdc
Black Bezel Swivel Bracket			
81864/HO	Spot	2500	12 - 24Vdc
81866/HO	Medium Flood	2500	12 - 24Vdc
81867/HO	Hybrid	2500	12 - 24Vdc

Accessories


HW02A Hardware Kit | C-Bracket 98189 Hardware Kit | Swivel Bracket









C-Bracket






Beam Patterns









For more lighting and electronic solutions, please check out our catalogue.