# XWL-810 Series | Soft Start COMPACT LED WORK LIGHT | 1260 LUMENS







## **Feature**

- Soft start function reduces the "in rush current"
- Die cast aluminum housing, polycarbonate lens and high impact bezel
- IP68 & IP69K
- Low current draw
- · Constant current circuit draw
- 4 beam patterns
- 50,000+ hours LED service life



## Benefit

Improves electronic component life and eases the load on existing wiring and battery.

the bright light, improving safety.

Virtually unbreakable.

Will withstand dust, dirt, sand, and water submersion.

Energy efficient, save on fuel costs.

Light does not dim even if voltage fluctuates.

Get light where it's needed most.

Long lasting investment, quality product.







### **Specifications**

Operating Voltage: 12 - 24Vdc **Operating Current:** 1.2A @ 12Vdc 0.6A @ 24Vdc

Power Consumption: 14W

-40°C to +80°C Temperature Range: Ingress Protection: IP68 & IP69K 1.3lbs (0.6kg) Weight:

Die Cast Aluminum Alloy A380 | Black E-Coat Housing:

Lens: Automotive Optical Grade

Hard-Coated Polycarbonate

6" Wire Connection:

Polarity: Reverse Voltage Protected

Vibration Resistance: 10-500Hz @ 5Grms

Mounting: C-Bracket (Powder Coated Steel)

Swivel Bracket (Zinc Dichromate Plating)

EMC EN 13309: 2010 EMC Rated:


Part #	Beam Pattern	Lumens	Operating Voltage	
81801	Spot	1260	12 - 24Vdc	
81802	Wide Flood	1260	12 - 24Vdc	
81803	Medium Flood	1260	12 - 24Vdc	
81804	Hybrid	1260	12 - 24Vdc	
Swivel Bracket				
81811	Spot	1260	12 - 24Vdc	
81812	Wide Flood	1260	12 - 24Vdc	
81813	Medium Flood	1260	12 - 24Vdc	
81814	Hybrid	1260	12 - 24Vdc	

#### Accessories

HW02A Hardware Kit | C-Bracket 98189 Hardware Kit | Swivel Bracket


98195 Easy Grip Handle - Black | Blue | Orange









C-Bracket





**Swivel Bracket** 

#### **Beam Patterns**











For more lighting and electronic solutions, please check out our catalogue.